halo®

PRODUCTSHEET

Productsheet 'Halo' Pod – Phase 1

USP

- Design freedom
- Acoustical performance
- Unique Design
- Optimal inner size
- Reconfigurability
- Synergy Maars Portfolio
- Easy installation
- Sustainability

THE PODS

Halo 1 – Class A

Outside Dimensions:
1200mm x 1200mm x 2360mm

Inside Dimensions:
1036mm x 1036mm x 2200mm

Acoustics: According to ISO23351-1 up to class A

Extraction rate: 70 CFM

Halo 2 – Class B*

Outside Dimensions:
1200mm x 1200mm x 2300mm

Inside Dimensions:
1036mm x 1036mm x 2200mm

Acoustics: According to ISO23351-1 up to class B*

Extraction rate: 70 CFM

Estimated value

halo®

maars LIVING WALLS®

HALO

Design Freedom
- Create yourself
- Specify your type of wall
- Specify your finish
- Custom
- Flexible

Acoustics
- Maars has a lot of knowledge on acoustics
- Internal testing facilities
- Up to class A according to ISO 23351-1
- Maars always strives for higher values
- PODS are a combination between isolation and absorption

Unique Design
- Bespoke and unique design
- Best of both worlds
- Unique integrations of lightning and ventilation

Optimal inner size
- Comfortable working space
- Wellbeing of user comes first
- Inner volume

Synergy Maars Portfolio
- Matching Maars walls and doors in finishes
- Matching Maars walls and doors in sizes

Easy Installation
- Dual installation approach
- Using prefab cassettes

Sustainability
- Easy reusable
- Reuse of elements and cassettes
- Glass and steel walls are C2C certified

Reconfigurability
- Modular solution
- Easy adjustable

halo®

maars LIVING WALLS®

SPECIFICATIONS / OPTIONS

Doors
Glazed doors
- Frameless Glass Door
  - 12 mm acoustic laminated tempered glass Rw 35 dB
- Slim framed glass door
  - Rw 37 dB

Lock options
- Bar-pull
- Lever
  - Optional Cylindrical lock

Ceiling
- Integrated LED beam lighting
- Perforated steel
- Surrounded double Halo LED lighting
  - Daylight

Floor
- Carpet tiles
- Additional flooring with 20mm install tolerance
- (without floor) ADA Compliant

Ventilation
- Centrifugal
- Motion sensor controlled
- Standard 70 CFM

maars LIVING WALLS®

halo®

FINISHES

Solid panel
- Powder coated
- Fabric on steel
- Acoustical perforated

Glass panel
- Bi-block
  - 6 + 8mm acoustic layered
  - 6 + 6 se

Carpet tiles
- See the end of this product sheet for all carpet finishes

Fabric
- Available for inside panels only.
- Different fabric finishes
- See the end of this product sheet for all finishes.

FURNITURE
- Integrated Desk – height adjustable
- Excluded seating

POWER
- Power outlet bottom panel
- USB/universal 220V-socket inside POD under desk

ACOUSTICS

- Internal tested according to ISO 23351-1 up to value

MATCHING MAARS PORTFOLIO

Create modern interior architecture and any combinations with the Maars product looks of our wall systems

- Combine different PODS
- Combine different walls and doors
- Any configuration possible
- Reach out to Regional Sales Manager for the possibilities.

halo®

maars LIVING WALLS®

SUSTAINABILITY

- Easy reuse
- Flexible
- Modulair concept – cassette system

INSTALL

- 1 POD = 2 hours with 2 persons (based on cassettes)

CONTACT

Reach out to our Product Specialist to learn even more about the possibilities our products can offer.

NEXT PHASES

- 2 person POD
- 4 person POD

halo®

maars LIVING WALLS®

FABRIC FINISHES

OC 009	OC 006	OC 004	OC 005	OC 003	OC 001
OC 016	OC 012	OC 014	OC 010	OC 011	OC 008
OC 122	OC 019	OC 020	OC 017	OC 018	OC 015
OC 029	OC 027	OC 025	OC 026	OC 023	OC 024
OC 038	OC 036	OC 033	OC 034	OC 031	OC 023

halo®

Technical Specifications:

maars LIVING WALLS®

FABRIC FINISHES

OC 320	OC 041	OC 042	OC 039	OC 040	OC 100
OC 425	OC 557	OC 755	OC 259	OC 289	OC 800
OC 028	OC 007	OC 021	OC 030	OC 035	OC 002

Technical Specifications:

halo®

CARPET TILE SAMPLES

008	**128**	**138**	**168**	**178**	**198**
228	**258**	**268**	**448**	**578**	**588**
598	**628**	**638**	**648**	**738**	**748**
768	**778**	**788**	**878**	**908**	**928**
948	**958**	**968**	**978**	**988**	**998**

Technical Specifications:

halo®

maars LIVING WALLS®